

MATERIAL SAFETY DATA SHEET

IDENTIFICATION OF THE SUBSTANCE/PREPARATION, REVISION NUMBER AND DATE

Product Name: Fast dry black ink for rewinding package

Product Code: CBK

Revision No.:EJ20131009CBK

Date:09/10/2013

COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS(nl-not listed in CHIP)

Chemical Name	%	CAS Number	EEC No	Hazard Symbol	R Phases
Synthetic Resin	15-25	N/A	N/A	N/A	N/A
Medium-boiling petroleum solvent	45-70	N/A	N/A	N/A	N/A
Pigment	4-10	N/A	N/A	N/A	N/A
Additives	3-10	N/A	N/A	N/A	N/A

HAZARDOUS IDENTIFICATION

Classification: Flammable. liquid and vapors

Main Health Hazards: May cause drowsiness and dizziness. Harmful to aquatic organisms with long lasting effect

FRIST AID

Inhalation: remove casualty to fresh air.

Skin Contact: wash from skin using soap and water.

Eye Coact: Flush thoroughly with water. If soreness or redness persists, seek medical attention.

Ingestion: DO NOT induce vomiting, encourage casualty to drink water. Seek medical advice.

Do not use:

FIRE FIGHTING MEASURES

Flammability:Product is classified as flammable (Flash Point 39°C).

Combustion products: Oxides of Carbon.

Extinguishing media: In the event of fire use CO2, Foam, Dry Powder, or Vaporizing Liquid.

Do not use:

Measures:

ACCIDENTAL RELEASE MEASURE

Mop or soak up spillage's in absorbent material. Dispose of in accordance with Local Authority Regulations.

HANDLING AND STORAGE

Handling: Avoid prolonged skin contact. Wear gloves and safety glasses if splashing is likely.

Fire Prevention: Avoid heat and sources of ignition

Storage: Normal cool warehouse conditions. Keep in closed container.

PHYSICAL AND CHEMICAL PROPERTIES

Form:Black Coloured Liquid with irritating smell

PH: n/a

Boiling Point: 105-215°C

Flash point: 39°C

Melting Point: -10°C

Solubility in water: Soluble in water

Density:Approx.0.93

Auto ignition Point:380°C

Explosive Limits:Lower 1.1%; Upper 9.4%

STABILITY AND REACTIVITY

Chemical reactivity: None

De-composition products: None

Materials/conditions to avoid: Exposed to fire or high temperature may may create fire or explosion hazard.

And produce hazardous decomposition products. Keep away from the following materials to prevent strong exothermic reactions:oxidizing agents, strong alkaline, strong acids.

DISPOSAL CONSIDERATIONS

Consult Local Authority for regulations regarding waste disposal

TRANSPORT REGULATIONS

Proper shipping name: Printing ink, flammable

Packing group:III

UN Number:UN1210

IMDG class:3.2

IMDG code:

RID/ADR:ADR Item 5(b)

ICAO/LATA class:3

Hazard warning sign:Flammable Liquid

Marine pollutant:

Regulatory information

CHIP Labeling -

Symbol:

Hazard: Irritant

Contains:

St. Andrews Cross

Rish Phrase:

Other suggested labeling:Avoid contact with eyes

OTHER INFORMATION

This safety data sheet has been updated to comply with CHIP regulations. The information is based solely on the data provided by the suppliers of the materials used and/or recognised technical sources, not on the mixture itself and is believed to be correct as of this dat. No warranty is expressed or implied regarding the accuracy of the data.

YUCHANG INDUSTRIAL CO., LTD.

Tel. 86-21-6049 8081

Fax. 86-21-5997 0419